

# NOVAX AdBlue<sup>®</sup> Specification

|  |               |                   |
|--|---------------|-------------------|
| Urea / 尿素  | 31.8-33.2     | % by weight       |
| Alkalinity as NH <sub>3</sub> / NH <sub>3</sub> 濃度 | max.0.2       | % by weight       |
| Biuret / 縮二尿                                       | max.0.3       | %                 |
| Insolubles / 不溶物                                   | max.20        | mg/kg             |
| Aldehyde / 乙醛                                      | max.5         | mg/kg             |
| Phosphate (PO <sub>4</sub> ) 磷酸鹽                   | max.0.5       | mg/kg             |
| Aluminium / 鋁                                      | max.0.5       | mg/kg             |
| Calcium / 鈣  | max.0.5       | mg/kg             |
| Iron / 鐵   | max.0.5       | mg/kg             |
| Copper / 銅   | max.0.2       | mg/kg             |
| Zinc 鋅   | max.0.2       | mg/kg             |
| Chromium / 鉻                                       | max.0.2       | mg/kg             |
| Nickel / 鎳   | max.0.2       | mg/kg             |
| Magnesium / 鎂                                      | max.0.5       | mg/kg             |
| Sodium / 鈉   | max.0.5       | mg/kg             |
| Potassium / 鉀                                      | max.0.5       | mg/kg             |
| Density at 20 C / 比重                               | 1087.0-1093.0 | kg/m <sup>3</sup> |
| Refractive index at 20 C / 折射率                     | 1.3814-1.3843 | (-)               |

The analytical methods are defined in ISO 22241 (version 2006)

**NOVAX Material & Technology Inc.**

No.31, Ln. 142, Sec. 2, Nankan Rd., Luzhu Dist.,

Taoyuan City 33855, Taiwan (R.O.C.)

Tel : +886-3-311-5988 Fax : +886-3-311-5288